

# TOSHIBA

Leading Innovation >>>

**e-STUDIO™ 2508A**

**e-STUDIO™ 3008A**

**e-STUDIO™ 3508A**

**e-STUDIO™ 4508A**

**e-STUDIO™ 5008A**

- > Black & White Multifunction Printer
- > Up to 50 PPM
- > Small/Medium/Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



# BNE

**TOGETHER  
INFORMATION**

# e-STUDIO™ 2508A/3008A/3508A/4508A/5008A

## Main Specifications

<b>Copy System</b>	Indirect Electrostatic Photographic Method
<b>Display</b>	9" Colour WVGA Touch Screen Tilting Display
<b>Copy Speed</b>	25/30/35/45/50 PPM (A4)
<b>First Copy Out</b>	4.3/4.3/3.6/3.6/3.6 Seconds
<b>Warm-Up Time</b>	Approx. 20 Seconds
<b>Copy Resolution</b>	2,400 x 600 dpi with Smoothing
<b>Stack Feed Bypass</b>	100 x 148 mm to A3, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 1,200 Sheets/Max. 3,200 Sheets (w/Optional LCF)
<b>Original Feed</b>	Optional 300-Sheet DSDf or 100-Sheet RADF
<b>Scan Speed &amp; Weights</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour)(35-209 g/m <sup>2</sup> ) RADF Scan: Up to 73 IPM (Monochrome or Colour), Simplex: 35-157 g/m <sup>2</sup> Duplex: 50-157 g/m <sup>2</sup>
<b>Max. Original Size</b>	A3
<b>Paper Feed Sizes /Weights</b>	Drawer 1, Drawer 2: 550 Sheets-A5-R to A3 (60-256 g/m <sup>2</sup> ) Stack Feed Bypass: 100 Sheets-100 x 148 mm to A3 (60-256 g/m <sup>2</sup> ) Opt. 550-Sheet Paper Feed Pedestal-A5-R to A3 (60-256 g/m <sup>2</sup> ) Opt. 550-Sheet Drawer for PFP-A5-R to A3 (60-256 g/m <sup>2</sup> ) Opt. Envelope Cassette for PFP-Approx. 50 Envelopes/550 Sheets-A5-R to A4-R (60-256 g/m <sup>2</sup> ) Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-A4 Only (64-105 g/m <sup>2</sup> ) Standard Automatic Duplex Unit (60-256 g/m <sup>2</sup> )
<b>Duplex Reproduction Ratio</b>	25% to 400%
<b>Weight</b>	Approx. 55 kg for e-STUDIO2508A/3008A Approx. 58 kg for e-STUDIO3508A/4508A/5008A
<b>Approx. Dimensions</b>	585 (W) x 585 (D) x 787 (H) mm
<b>Toner Yield</b>	±43.9K (5% Coverage)
<b>PM Cycle/Duty Cycle</b>	±120K/130K/140K/150K/180K
<b>Drum Type/Yield</b>	±120K/130K/140K/150K/180K
<b>Developer Yield</b>	±120K/130K/140K/150K/180K
<b>Power Source</b>	220-240 Volts, 50/60 Hz, 8 Amps
<b>Power Consumption</b>	Maximum 2.0 kW (220-240V)
<b>CPU</b>	Intel Atom™ 1.33GHz (Dual-Core)
<b>Memory</b>	4GB
<b>Hard Disk Drive</b>	320GB Self-Encrypting Drive Toshiba HDD

## e-Filing Specifications

<b>Operation Method</b>	Colour Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## e-BRIDGE Print Specifications (Option)

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Speed</b>	25/30/35/45/50 Pages Per Minute (A4)
<b>Print Resolution</b>	600 x 600 dpi (1 bit) 2,400 x 600 dpi (with Smoothing) 1,200 x 1,200 dpi (2 bit) 3,600 x 1,200 dpi (with Smoothing) PS3 Only
<b>Operating Systems</b>	Windows® Vista, Windows 7, 8, 8.1, 10, Windows Server 2008/R2, Windows Server 2012/R2, Macintosh® (Mac OS x 10.4, 10.5, 10.6, 10.7, 10.8, 10.9, 10.10, 10.11), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk® for Macintosh Environments
<b>Interface</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional 802.11b/g/n, Wireless LAN/Bluetooth
<b>Wireless Device</b>	AirPrint, Mopria, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
<b>Device Management</b>	Top Access, EFMS 6.2 (e-BRIDGE Fleet Management Software)
<b>Account Control</b>	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List and User Function
<b>Environmental Stds. Certification</b>	Energy Star (V2.0), EPEAT Gold, Blue Angel Mark (RAL UZ-171, MFD), RoHS WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP



This is Class 1 laser product complying with IEC60825-1.

Windows is a registered trademark of Microsoft Corporation in the United States and other countries. iPad, iPhone, iPod, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc. IOS is a registered trademark of Cisco in the United States and other countries and is used under license. Android is a trademark of Google Inc. All other brand and/or product names are trademarks of their respective owners. Mention of third party products herein is for informational purposes only.

This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2016 TOSHIBA TEC CORPORATION All rights reserved.

As an ENERGY STAR Partner TOSHIBA TEC CORPORATION has determined that this multifunctional device model meets the ENERGY STAR guidelines for energy efficiency.

## Distributed by



## Business Machines & Equipment

10 Taher Tower (2nd Floor), Suite No: 319-321, Gulshan-02, Dhaka - 1212, Bangladesh  
Tel: 02 9890665, 9886192, Hotline: 01755601720, 01748981082, 01755601735  
Fax: 02 9888142, E-mail: info@bmebd.com, bmetoshiba@gmail.com  
Web: www.bmebd.com

## Scan Specifications (Option)

<b>Scan Speed</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour) RADF Scan: Up to 73 IPM (Monochrome or Colour)
<b>Scan Modes</b>	Full Colour, Auto Colour, Monochrome, Grayscale
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.), Searchable PDF (Opt.) Colour/Grayscale: TIFF-Multi/Single Page, PDF-Multi/Single Page, XPS-Multi/Single Page, Slim PDF, JPEG, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.), Searchable PDF (Opt.)

## Facsimile Specifications (Option)

<b>Compatibility</b>	Super G3, G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations /Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## Accessories (Options)

### Platen & Document Feeder Options-1

DSDf	MR4000
RADF	MR3031
Platen Cover	KA5005PC

### Desk & Additional Paper Options-2

Paper Feed Pedestal	KD1058
Drawer Module	MY1048
Envelope Cassette Option	MY1049
Large Capacity Feeder	KD1059A4
Desk/Stand	MH5000

### Finishing Options-3

Inner Finisher	MJ1042
50-Sheets Staple Finisher	MJ1109
Saddle-Stitch Finisher	MJ1110
Hole Punch Unit for MJ1042	MJ6011
Hole Punch Unit for MJ1109/MJ1110	MJ6105
Bridge Kit	KN5005
Job Separator	MJ5014
Job Separator	MJ5015
Staple Cartridge for Finisher	STAPLE2400
Staple Cartridge for Saddle	STAPLE3100

### Connectivity/Security Options

FAX Unit/2nd Line for FAX Unit	GD1370
Wireless LAN/Antenna/Bluetooth	GN4020
Accessory Tray	GR1250
Panel 10-Key Option	GR1260
Printer/Scanner Enabler	GM2280
Data Overwrite Enabler	GP1070
Card Reader Holder	GR1290
USB Hub Option	GR1270
Meta Scan Enabler	GS1010
IPsec Enabler	GP1080
Unicode Font Enabler	GS1007
Embedded OCR Option	
Single License	GS1080
Five Licenses	GS1085
Multi-Station Print Solution Option	
Single License	GS1090
Five Licenses	GS1095

### Miscellaneous Options

Accessible Arm	KK2560
Work Tray	KK5005
Harness Kit for Coin Controller	GQ1280
Manual Pocket	KK5008



TOSHIBA TEC SINGAPORE.  
www.estudio.com.sg

All company and/or product names are trademarks and/or registered trademarks of their respective owners. All features and specifications described in this brochure are subject to change without notice.

©2016 TOSHIBA TEC CORPORATION. All rights reserved.

R140611P0200-TTEC