

DISAB Vacloader



(This unit is equipped with options)

CENTURION LN14

A truck mounted unit that can transport bulk materials and liquids by vacuum through a hose system with a diam up to 200 mm.

The vacuum loader is designed and adapted for mounting onto a four-axle truck chassis with two front axles

The material tank and filter compartment are combined and the dust from the filter compartment is emptied through a hatch at the same time as the tank is tilted.

Technical data

Diesel engine

A six cylinder turbocharged diesel engine complying with the EU Stage IV / EPA Tier 4f emission requirements.

Make Volvo D8 TAD873VE

Cylinder volume 7.7 I

Power 235 kW/320 hp Max engine speed 2200 rpm/min

Injection SCR technology and a cooled EGR

Charging system 24 VDC
Engine cooler Water to air
Air charging cooler Air to air

Vacuum pump Kaeser Omega 83 PV

 $\begin{array}{lll} \text{Max.vacuum} & -950 \text{ mbar} \\ \text{Air volume, unloaded} & 8100 \text{ m}^3\text{/h} \\ \text{Air volume (-500mbar)} & 7100 \text{ m}^3\text{/h} \\ \text{Operating speed} & 1100 - 2650 \text{ rpm} \end{array}$

Max power required 220 kW

Main filter system 2x35 galvanized cages with filter socks

in needled polyester -glazed surface.

Filter area 26 m²

Safety filter system 3 filter cartridges - 33 m² located in the machine

house

Tank Gross volume 10000 litres

Tailgate Hydraulically operated and locked

Tipping system Hydraulic front cylinder, double acting system

Level guards Wet resp dry level guards









Technical changes without notice

Telephone + 46 413 55 43 00

Telefax + 46 413 55 43 01