



AN ISO 9001:2008 CERTIFIED COMPANY

OUR MISSION SERVICE WITHIN 24 HOURS CALL:1800 121 0930 (9.30 AM TO 5.30 PM ON WORKING DAYS) | FOR PRODUCT ENQUIRY CALL: 1800 123 0930



FOR PRODUCT ENQUIRY CALL
1800 123 0930



Hand operated sealing machines

Ideal for sealing heat sealable poly pouches | Hand operated Impulse (instant) sealing | Hot bar sealers for laminated pouches | Adjustable electronic timer | Audio visual sealing indicators | Suitable for packing solids, granules and powders | Round element option for simultaneous sealing and cutting

Technical specifications

Model	Seal (mm)		Power		Dimension (mm)			Weight Kg.
	Length	Width	V	VA	L	B	H	
Impulse Sealers								
125D	122	-----	240	200	240	85	155	1.7
190HP	190	1.6 x 2	240	345	305	85	155	2.75
190HW	190	3	240	345	305	85	155	2.75
200Dv2	200	1.6	240	215	305	85	155	2.5
200HB	200	1.6	240	245	305	85	155	2.7
250D	250	1.6	240	320	350	85	155	2.85
300D	300	1.6	240	340	405	85	155	3.2
300HB	300	1.6	240	390	405	85	155	4.3
300HW	300	3	240	500	405	85	155	4.4
400D	400	1.6	240	525	535	85	155	4.6
400HB	400	1.6	240	565	535	85	155	4.7
400HW	400	3	240	600	535	85	155	5
500HB	500	1.6	240	545	630	85	155	5.6
600HB	600	1.6	240	710	720	85	155	6.5
Hotbar Sealers								
200 HH	200	11	240	190	340	85	155	2.6
300 HH	300	11	240	290	410	85	155	3.0

*Indicated dimensions are without packing

Pictures shown may vary from actual products.

Foot operated sealing machines

Adjustable electronic timer
Tiltable sealing jaw
Adjustable bag rest
Ease of operation
High productivity
Visual indication during sealing
Audio indication at the end of sealing
Hot bar sealer with energy regulator for sealing laminated pouches



Technical specifications

Model	Seal (mm)		Power V	Power W	Dimensions (mm)			Weight (kg)
	Length	Width			L	B	H	
Impulse Sealers								
QS 200 F	200	1.6	240	280	660	620	1050	17
QS 200 FE	200	5	240	470	660	620	1050	18
QS 200 FP	200	3x2	240	750	660	620	1050	22
QS 300 F	300	1.6	240	400	660	620	1050	19
QS 300 FE	300	5	240	800	660	620	1050	22
QS 300 FP	300	3x2	240	800	660	620	1050	24
QS 400 F	400	1.6	240	470	660	620	1050	20
QS 400 FE	400	5	240	720	660	620	1050	23
QS 500 F	500	1.6	240	560	660	620	1050	20
QS 500 FE	500	5	240	750	660	620	1050	23
QS 600 F	600	1.6	240	650	700	620	1050	23
QS 600 FE	600	5	240	920	700	620	1050	26
QS 900 F	900	1.6	240	950	1000	620	1050	30
Hotbar Sealers								
200 FH	200	12	240	200	660	620	1050	24
300 FH	300	12	240	270	660	620	1050	26
400 FH	400	12	240	350	660	620	1050	28

Delta series (Economy)

No tilting facility; F D- Standard model, FE D-5mm sealing Width, FP D- Two parallel 3mm wide seals, FHE D- Hot bar sealers



Technical specifications

Model	Seal (mm)		Power V	Power W	Dimensions (mm)			Weight (kg)
	Length	Width			L	B	H	
Impulse sealers								
300 F D	300	1.6	240	400	500	500	1000	17
300 FE D	300	5	240	600	500	500	1000	18
300 FP D	300	3x2	240	800	500	500	1000	19
400 F D	400	1.6	240	470	500	500	1000	22
400 FE D	400	5	240	720	500	500	1000	24
Hot bar sealers								
200 FHE D	200	12	240	130	500	530	930	14
300 FHE D	300	12	240	200	500	530	930	17
400 FHE D	400	12	240	200	500	530	930	20



Automatic Impulse-Sealing Machine

The stylish Sepack Impulse Sealers are made to perform continuous, effortless and consistent sealing of heat sealable plastic bags. It produces smooth sealing on a wide variety of plastic materials of various thickness.

Find applications in food packaging, supermarkets, pharma & engineering industries.



Mobile sealer

- For packing heavy bags
- Ideal for tea sacks, chemicals, spices etc.
- A mobile machine can reach to the filled bag
- Height adjustability 0.3 to 1.3m

Technical specifications

Model	Seal (mm)		Power		Dimensions (mm)			Weight (Kg)
	Length	Width	V	W	L	B	H	
900 MSE	900 mm	5mm	240	1.04 kw	1150	305	1500	60



Bed sealer

- can seal up to a length of six feet 5mm sealing width
- Reverse bend rocker arm for uniform- sealing from one end to the other
- Equipped with bearing mounted lever to achieve maximum pressure during sealing

Technical specifications

Model	Seal		Power	
	Length	Width	V	W
1800 TM	1800 mm	5	240	2.7 Kw
1200 TM	1200 mm	5	240	1.5 Kw

Foil sealers

- For pilfer evident and leak proof sealing of aluminum foils on cups, cans, bottles, plastic containers and trays
- Height adjustability and provision for heat control

Strong cups, cans and bottles can be sealed without extra attachments. Flimsy Cups and trays require extra support at the bottom of the neck, otherwise the cup/neck may be crushed during sealing operation. The support has to be matched with the shape of the cup to be sealed. (Provide dimensional sketches or samples for design of appropriate support)

Technical specifications

Model	Height of the Containers	Sealing Dia Max	Power Watts	Voltage	L B H (mm)			Weight Kg
					L	B	H	
FS 1045	0 to 450mm	90mm	200	AC 240	560	250	650	8.5
FS 1545	0 to 450mm	140mm	300	AC 240	560	250	650	11
FS 2045	0 to 450mm	190mm	450	AC 240	560	250	650	13.5
FSD 1045	0 to 170 mm	90mm	200	AC 240	460	170	250	4
FSD 1545	0 to 170 mm	140mm	300	AC 240	460	170	250	4.5



Foil Sealer (FS)



Foil Sealer Delta



Hand wrapper HW 450

- Ideal for wrapping cling film
- Suitable for super markets, fruit stalls, Bakeries, frozen foods etc
- Enhanced display on the shelf

Technical specifications

Model	Hand wrapper - HW 450
Voltage	240 V 1Phase
Power	50W
Film width	up to 450mm



Hot air gun

The Stylish Hot Air Gun from Sepack is generally used for shrink wrapping of objects like bottles, containers, tray, hardware items & spare parts. Shrink wrapping provides an attractive pilfer proof shape hugging protection.

Technical specifications

Air flow	: 250/500LPM
Temp	: 400°C/550°C
Voltage	: 240V/50Hz
Power	: 1600W



Carton sealer

A hand held tool for dispensing BOPP adhesive tapes over boxes, containers etc.

Sepack Clip master & Strap master makes an ideal combination of hand tools for 'crimping the seal into place' effortlessly. Used for steel sealing clips.

SEPACK CLIPMASTER STRAPPING SEALER



SEPACK STRAPMASTER STRAPPING TENSIONER



Clip sizes: 0.6mm to 0.9mm Thick Steel Clip, 14mm - 19mm Width
Straps size: 0.6mm to 0.9mm Thick, PP Strap - 13mm - 19mm Width
Sealing type: Double Notch



Sepack SmartCode 4L

Offers smart economical coding solution for pouches, labels etc.
Supported letter types: Polymer (4mm)
Max No of Lines: 4
Max Print Height: 55mm
Ink Type: Anti Freeze 2R Grade(Black)