



## E LED 500 Mobile Opeprating Light with Battery



## Product Feature:

- Germany LED Light source pass through high-performance OSRAM lens
- 2.Option balance arm :Ondal Square Arm, Ondal Round Arm , Luxury
- Square Arm and Economy Round Arm
- 3. The Color temperature is adjustable from 3500k to 5000k by four levels while maintaining the color rendering index of Ra95.
- 4. The minimal life expectancy of each Led is 50.000 hours
- 5.Options:2~3hours back up battery, wall-mode arm, mobile-model base remote control, touch-screen , HD camera system.



( SPECIFICATIONS FOR LED LIGHT)		
(Model)	E LED 700	E LED500
(Central Illuminance)	40,000~150,000Lux	40,000~120,000Lux
(Focusable light-field within 1m distance)	120~300mm	
(Colour temperature)	3500~5000K	
( Depth of Focus)	>700mm	
(Colour index Ra)	95	
(Power Supply)	110~240V 50/60Hz	
(Effective bulb service life)	>50,000h	
(Diameter of lamp housing)	700mm	500mm
(power consumption (W))	60	36
(Installation height ceiling type)	280~320 cm	

## Details Picrture







Light Base

Battery

Control Pannel

## Other Type







E LED 700 Ceiling Type

E LED 500 Ceiling Type

E LED 700/500 Ceiling Type