


Wide spread network of 800+ dealers and 46 channel partners make *Jyoti Ek Kadam Aage* reach every corner of the country to provide consistent product support.



www.madhavkrggroup.com

@ For assistance : 97799-15000

Join us on : @madhavkrg

Follow us on : @Madhavkrggroup

Madhav KRG Ltd

Corp Office:

1st Fl., The Celebration Bazaar, G.T Road, Khanna, Punjab

Works:

Vill. Akalgarh, Amloh-Bhadson Road, Dist. Patiala, Punjab

New Delhi Office:

1002-03, Aggarwal Millenium Tower-I, Netaji Subhash Place, Pitampura, New Delhi





Proven Quality.
Solid Trust.

MADHAV KRG GROUP



TEMPCORE SG

TMT BAR

JYOTI TEMPCORE 56 🛗

















TEMPCORE SG

TMT BAR

// JYOTI TEMPCORE SG 👼 / / / / / JYOTI TEMPCORE SG 👼 / / / / / / JYOTI TEMPCORE SG 👼 / / / / / / JYOTI TEMPCORE SG 👼

MADHAV KRG GROUP



6.5 Lacs Production Capacity of Steel



The 5S ADVANTAGE TMT Rebar






Minimum 18% Elongation (Lachak)



JYOTI TEMPCORE 56 👼







/ JYOTI TEMPCORE SG 👼 / / / / / / JYOTI TEMPCORE SG 👼 / / / / / JYOTI TEMPCORE SG 👼 / / / / / JYOTI TEMPCORE SG 👼

Resistance
Best Control on Chemistry of the Liquid Iron



Super Fine Quality
with Zero Impurities & absolute removal of Harmful Gases

BENEFITS OF WORLD FAMOUS LRF TECHNOLOGY



Phosphorous & Sulphur the most harmful impurities are controlled in much better manner, ensuring an Impurity Free Final Product.

YOTI Tempcore SG TMT is produced by World acclaimed Tempcore Technology duly certified by, CRM Belgium.

Absolute removal of Harmful Gases (Oxygen, Hydrogen, Nitrogen) for environmental benefits.

Internal Defects which are not mentioned in BIS 2830 (Billets) are removed to an extent of 100%.

lyoti Tempcore SG TMT has 100% Bundle Weight which is as per BIS 1786 standard (92-96 KG on 12 Meter Length)

30 Ton Capacity of LRF for volume and fast production.

PRODUCT SPECIFICATIONS

TRADE MARK GRADES DIAMETER Jyoti Tempcore -6, 8, 10, 12, 16, 20, Jyoti Tempcore SG 1786

Fe 500, Fe 550, Fe 500D, Fe 550D 25, 28, 32, 36, 40 mm

PHYSICAL PROPERTIES

III DICHE I III	OI LITTILD		
SIZE	JYOTI SG STANDARD	I.S.I STANDARD	
5 MM	206 to 238 gm/mtr	204 to 240 gm/mtr	
в мм	380 to 400 gm/mtr	367 to 422 gm/mtr	
10 MM	580 to 605 gm/mtr	574 to 660 gm/mtr	
12 MM	850 to 880 gm/mtr	844 to 932 gm/mtr	
16 MM	1530 to 1595 gm/mtr	1501 to 1657 gm/mtr	
20 MM	2410 to 2490 gm/mtr	2394 to 2544 gm/mtr	
25 MM	3800 to 3899 gm/mtr	3735 to 3965 gm/mtr	

CHEMICAL PROPERTIES

SULPHUR 0.030 to 0.045 max CARBON 0.18 to 0.25 max MANGANESE 0.45 to 0.70 max PHOSPHORUS 0.030 to 0.045 max

MECHANICAL PROPERTIES

	PARAMETER	JYOTI TEMPCORE SG REBAR				
		500	500 D	550	550	
	Yield Strength	520 N/mm ²	520 N/mm ²	565 N/mm ²	565 N/mm ²	
	Tensile Strength	620 N/mm ²	620 N/mm ²	655 N/mm ²	655 N/mm ²	
	Elongation	18%	18%	18%	18%	