

Wide spread network of 800+ dealers and 46 channel partners make "Jyoti Ek Kadam Aage" reach every corner of the country to provide consistent product support.

info@madhavkrggroup.com

www.madhavkrggroup.com

For assistance : 97799-15000

Join us on : @madhavkrg

Follow us on : @Madhavkrggroup

Madhay KRG Ltd

Corp Office:

1st Fl., The Celebration Bazaar, G.T Road, Khanna, Punjab

Works

Vill. Akalgarh, Amloh-Bhadson Road, Dist. Patiala, Punjab

New Delhi Office:

1002-03, Aggarwal Millenium Tower-I, Netaji Subhash Place, Pitampura, New Delhi





Proven Quality.
Solid Trust.

MADHAV KRG GROUP



TEMPCORE SG

TMT BAR

















TEMPCORE SG

// JYOTI TEMPCORE SG 👼 / / / / / / JYOTI TEMPCORE SG 👼 / / / / / JYOTI TEMPCORE SG 👼 / / / / / JYOTI TEMPCORE SG 👼

MADHAV KRG GROUP




6.5 Lacs Production Capacity of Steel



The 5S ADVANTAGE TMT Rebar







JYOTI TEMPCORE 56 5








the Liquid Iron

/ JYOTI TEMPCORE SG 🛗 / / / / / / JYOTI TEMPCORE SG 🛗 / / / / / JYOTI TEMPCORE SG 🛗 / / / / JYOTI TEMPCORE SG 👼



Super Fine Quality
with Zero Impurities
& absolute removal
of Harmful Gases

BENEFITS OF WORLD FAMOUS LRF TECHNOLOGY



Phosphorous & Sulphur the most harmful impurities are controlled in much better manner, ensuring an Impurity Free Final Product.

JYOTI Tempcore SG TMT is produced by World acclaimed Tempcore Technology duly certified by, CRM Belgium.

Absolute removal of Harmful Gases (Oxygen, Hydrogen, Nitrogen) for environmental benefits.

Internal Defects which are not mentioned in BIS 2830 (Billets) are removed to an extent of 100%.

Jyoti Tempcore SG TMT has 100% Bundle Weight which is as per BIS 1786 standard (92-96 KG on 12 Meter Length)

30 Ton Capacity of LRF for volume and fast production.

PRODUCT SPECIFICATIONS

TRADE MARK	GRADES	DIAMETER	
Jyoti Tempcore SG isi	Jyoti Tempcore -	6, 8, 10, 12, 16, 20,	
	Fe 500, Fe 550, Fe 500D, Fe 550D	25, 28, 32, 36, 40 mm	

PHYSICAL PROPERTIES

I III SICALI NOI LI	VIII-D	
SIZE	JYOTI SG STANDARD	I.S.I STANDARD
6 MM	206 to 238 gm/mtr	204 to 240 gm/mtr
8 MM	380 to 400 gm/mtr	367 to 422 gm/mtr
10 MM	580 to 605 gm/mtr	574 to 660 gm/mtr
12 MM	850 to 880 gm/mtr	844 to 932 gm/mtr
16 MM	1530 to 1595 gm/mtr	1501 to 1657 gm/mtr
20 MM	2410 to 2490 gm/mtr	2394 to 2544 gm/mtr
25 MM	3800 to 3899 gm/mtr	3735 to 3965 gm/mtr

CHEMICAL PROPERTIES

CARBON 0.18 to 0.25 max	SULPHUR 0.030 to 0.045 max
MANGANESE 0.45 to 0.70 max	PHOSPHORUS 0.030 to 0.045 ma

MECHANICAL PROPERTIES

PARAMETER	JYOTI TEN	IPCORE SG RE	BAR	
	500	500 D	550	550
Yield Strength	520 N/mm ²	520 N/mm ²	565 N/mm ²	565 N/mm ²
Tensile Strength	620 N/mm ²	620 N/mm ²	655 N/mm²	655 N/mm²
Elongation	18%	18%	18%	18%