



Hubei YongXiang Agricultural Machinery Equipment Co.,Ltd

8 Rows 150L Pneumatic Seeder



The Pneumatic Seeders or Fertilizer Machine from YongXiang make you have the possibility to customize your professional agriculture implement according to your needs.

Multiple selection of hopper sizes, seeding shafts and seeding rows allow us to offer you a customized solution for every need and budget, and to save seeds, fertilizer volume and labor cost. The precise spreading of seeds, fertilizer and micro granules(1 to 10mm) helps you obtain excellent yield.

The 8 rows Pneumatic Seeders & Fertilizer machine spread material efficiently and in an environmentally friendly manner. The professional air seeders can be used in small and medium farms with different hopper size and seeding rows optional.

Using excellent intelligent central system with radar sensor to precise control

Email: sales@agro-yongxiang.com Website: www.agro-yongxiang.com



the seeding volume and the electrically regulated metering roller, the seed enters the air channel where the electric fan conveys it through plastic hoses to the dispersion plates, from there it is evenly distributed near the ground. This enables precise seeding or fertilizing even when the wind is blowing.

Advantages:

- Most seed types(rice, wheat, rapeseed, soybean sorghum.etc) can be released in broadcast and drill sowing.
- Precise metering and exact lateral distribution across the entire working width.
- Mounting options on most implements, such as seed drills, single grain machines, agriculture maintenance implements, soil tillage implements.
- Easy adjustment & comfortable calibration test with Smart tablet APP.

Description:

- 150L polyethylene hopper, capacity: 1 to 8 outlets(optional)
- Intelligent tablet APP control seeding volume precisely
- Adjustable seeds rate from 1 to 300kg / ha.
- Equipped with air blower driven by dual 12-volt electric motor.
- Shaft roller is driven by a stepping electric motor.
- The airflow delivery the seed into flexible plastic hoses evenly.
- Radar monitor and control seeding rate synchronizes tractor speed
- Multiple seed roller optional, Low hopper sensor alarm
- Robust construction, easy operate and install on most implements.
- Size: 85x78x87cm Weight: 90KGS Working Width: 1-6m