



BED MAT



Features:

- Fibre reinforced Rubber
- High tear strength
- High cut growth resistance
- Excellent impact resistance and added protection for the truck bed
- Skid minimizing surface
- Raised, surrounding edge design for containing spills
- Unique ribbed floor provides airflow & reduces moisture
- Easy, no-drill, drop-in installation
- Excellent durability

Technical Specifications

Properties	Standard Applied	Unit	Specification
Hardness	ASTM D-2240	Shore A	70-85
Tensile Strength	ASTM D-424	Мра	Min 6.0
Elongation at break	ASTM D-424	%	45
Tear Strength	ASTM D0624	Kgf/cm	Min 50
Cut Initiation	ASTM D430	Cycle	Min 100000
Application Temperature	ASTM 1329	°C	-40°C to +100°C



Manufactured and Marketed by:

ALP OVERSEAS PVT. LTD.

Corporate Office: Plot No. 32, Sector-18 HUDA, Gurgaon, Haryana - 122015 (INDIA) **Telephone**: +91-124-4731500 | **Website**: www.alpoverseas.com

Rajesh Arora: 9811015051 - (All India), Lokesh Abrol: 9815017505 - (North), Raj Shekhar: 9845095868 - (South),

Satish Mishra: 9920662926 - (West), Manab Dey: 9903406624 - (East)

^{*} We can make as per customize design & size