



8/12 Rows Rice Seeding Machine use rice direct seeding technology eliminates the trouble of raising and transplanting rice seedlings. the sowing accuracy is as high as 98%. Save time, labor, seeds, costs and increase benefits.

Save time and labor. Direct seeding of rice is direct sowing, just like wheat, eliminating the process of raising seedlings, and transplanting, and there is no need to occupy rice fields for raising seedlings.

Direct seeding of rice does not have the process of regreening and seedling injury, so the growth period is shorter than that of transplanted rice in the same period. Direct seeding of rice is simple and convenient, which is conducive to large-scale development.

The YongXiang SeedHub with Intelligent tablet APP, central control system and radar sensor ensures precise distribution even in windy conditions. Using the electrically controlled metering shaft, the seed enters the air channel where it is conveyed by the blower fan to the ends through plastic hoses. Using radar speed measurement and control control system to accurately control the sowing amount, the sowing accuracy is as high as 98%.



Description:

1. Direct rice seeding machine with 8/12 Rows optional
2. Smart Tablet APP control precise seeding volume
3. Easy to attach on most brand riding transplanter (Yanmar, Kubota, Iseki .etc)
4. Rice seed roller with seeding rate from 7.5-600kg/ha
5. 12V transplanter battery power supply
6. Stepless motor, tablet control box, radar sensor combined working for high precise seeding rate control
7. Only set the seeds rate in control tablet APP and seeder works
8. Seed Level, Seed rate and calibration, working width on control APP tab
9. Anti-blocking, leakage, empty box alarm device
10. Remain seeds discharge operation on control tab
11. Water ditcher and seeds line maker, conducive to the field water in/drainage

Seeding Machine Assembly	8 Rows	10 Rows	12 Rows
Rows	1- 8 Outlets	1-12 Outlets	1-12Outlets
Smart Tablet with YongXiang APP	10 inches	10 inches	10inches
Seeder Hopper	75 L	100 L	100 L
Radar Sensor	Yes	Yes	Yes
Seed Roller	Rice	Rice	Rice
Seeding Iron Plate	Yes	Yes	Yes
Seeds Drill Sowing assembly	Yes	Yes	Yes
Battery Cable	Yes	Yes	Yes
Lift switch	Yes	Yes	Yes
Plastic Hoses	Yes	Yes	Yes
Seed Electric Scale	Yes	Yes	Yes
Seed Weight Calibration Bag	Yes	Yes	Yes

Specification	8 Rows	10 Rows	12 Rows
Hopper Volume:	75L	100L	100L
Horse Power	>14.7 KW, Matching rice transplanter (6-row and above riding high-speed rice transplanter)		
Structural Type:	Suspension	Suspension	Suspension
Size:	920*2000*880mm	920*2500*880mm	920*3000*880mm
Working Area/Hour	0.4-1 hm ² /H	0.54-1.27 hm ² /H	0.6-1.54 hm ² /H
Operating Speed Range	2-5km/h		
Row Spacing	25 cm	25 cm	25 cm
Seeding Rate Range	7.5-600kg/ha		
Weight	135 kgs	145 kgs	155 kgs