



TRIMPHANT

TRIMPHANT
IMPEX PRIVATE LIMITED

NOW
TOTAL CONTROL
ON ANY ROAD



www.trimphanttyres.com



TRIMPHANT IMPEX

OUR COMPANY

Trimphant Impex Private Limited Is Established In Year 2010 And Since Then It Is Growing And Achieving New Goals With Its Committed Team Of Professionals And Will Keep Continuously Growing With Its Commitment Towards Customer Satisfaction With Good Quality Timely Delivery And After Sales Services.

"Make In India" Is The True Motivation And We Are Committed To Make Sure Our Clients To Give Good Services, Timely Shipment And After Market.

Our Presence In Global Market Is Expanding Day By Day And We Are Known Brand For Good Quality And In Terms Of Services.

We Believe In Long Terms Business Relationship With Customers So Always Serve The Client Is Best Possible Way To Keep Continue Business With Us.





OFF THE ROAD (OTR) TYRES



TRIPHANT
INDIA PRIVATE LIMITED



TIP-01

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	IP BAR	Cap Load (kgs)
13.00-24	14	TIP-01	8	336	1282	3.25	3020
14.00-24	14	TIP-01	8	362	1348	3.75	3400



TIP-02

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	IP BAR	Cap Load (kgs)
16.9-24	12	TIP-02	15	440	1310	2.6	3250
17.5L-24	12	TIP-02	15	445	1270	2.7	3450
19.5L-24	12	TIP-02	17	490	1325	2.3	3450
16.9-28	12	TIP-02	15	440	1410	2.6	3550
18.4-26	14	TIP-02	16	472	1425	2.9	4375



TIP-03

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	IP BAR	Cap Load (kgs)
15.5-25	12	TIP-03	12	395	1275	2.25	2650
17.5-25	14	TIP-03	14	445	1350	2.25	3080
17.5-25	16	TIP-03	17	520	1490	2.25	4000
23.5-25	20	TIP-03	19.5	595	1615	2	6000



TIP-04

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	IP BAR	Cap Load (kgs)
20.5-25	20	TIP-04	17	520	1492	4.5	9500
23.5-25	24	TIP-04	19.5	595	1617	4.75	12500
1600-25	32	TIP-04	11.25/2.0	430	1490	650	12500
1800-25	40	TIP-04	13.00/2.5	495	1615	700	17000

*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



AGRICULTURE TRACTOR FRONT TIRES



TRIPHANT
INDIA PRIVATE LIMITED



TIP-05

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	IP BAR	Cap Load (kgs)
4.00-8	6	TIP-05	3	114	425	TT	4.25	206
4.00-10	6	TIP-05	6	145	505	TT	2.2	375
5.00-12	6	TIP-05		127	545	TT	2.4	220
6.50/8-12	6	TIP-05				TT		
7.50-18	8	TIP-05	5.5	210	862	TT	3.7	950



TIP-06

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	IP BAR	Cap Load (kgs)
5.00-15	4	TIP-06	4	142	659	TT	2.8	365
5.50-16	6	TIP-06	4.5	172	748	TT	3.3	525
6.00-16	8	TIP-06	5.5	209	807	TT	3.7	875
7.50-16	8	TIP-06	6	214	803	TT	4.15	870
9.00-16	10	TIP-06	8	239	857	TT	3.9	1250
4.00-19	4	TIP-06	3	117	717	TT	2.4	355
6.00-19	6	TIP-06	4.5	817	817	TT	3.3	650
6.50-20	8	TIP-06	4.5	867	867	TT	3.1	730



TIP-07

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	IP BAR	Cap Load (kgs)
10.00-16	8	TIP-07	8	275	900	TT	2.8	1215
10.00-16	10	TIP-07	8	275	900	TT	3.4	1360
11.00-16	8	TIP-07	10	320	970	TT	2.5	1230



TIP-08

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	IP BAR	Cap Load (kgs)
5.50-16	6	TIP-08	4	152	712	TT	3.7	525
6.00-16	8	TIP-08	5.5	209	807	TT	2.8	750
6.50-16	6	TIP-08	4.5	182	767	TT	3.1	615
7.50-16	8	TIP-08	6	214	803	TT	4.15	870



TIP-09

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	IP BAR	Cap Load (kgs)
5.50-16	6	TIP-09	4	156	722	TT	3.7	525
6.00-16	8	TIP-09	5.5	203	819	TT	2.8	750
7.50-16	8	TIP-09	6	214	803	TT	4.15	870

*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



AGRICULTURE TRACTOR REAR TIRES



TRIMPHANT
INFRA PRIVATE LIMITED

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	Cap Load (kgs)	IP BAR
7.50-16	8	TIP-10	6	214	803	TT	1360	4.15
8.3-24	6	TIP-10	W7	211	995	TT	825	2.4
9.5-24	8	TIP-10	W8	241	1050	TT	1120	2.8
11.2-24	8	TIP-10	10	286	1102	TT	1250	2.4
12.4-24	8	TIP-10	11	316	1158	TT	1450	2.3
13.6-24	8	TIP-10	12	347	1212	TT	1500	1.9
14.9-24	8	TIP-10	13	379	1268	TT	1800	1.8
15.5/80-24	14	TIP-10	13	394	1262	TT	3150	3.5
16.0/70-20	14	TIP-10	14	418	1097	TT	2650	3.5
16.9-24	8	TIP-10	15	431	1337	TT	2060	1.7
14.9-26	8	TIP-10	13	378	1295	TT	1750	1.6
18.4-26	12	TIP-10	16	467	1450	TT	3000	2.3
16.9-34	12	TIP-10	15	431	1587	TT	2130	1.7
18.4-34	12	TIP-10	16	469	1652	TT	2300	1.4
18.4-34	12	TIP-10	16	469	1652	TT	2415	1.5
11.2-38	12	TIP-10	W 10s	288	1475	TT	1450	1.6
13.6-38	12	TIP-10	12	345	1570	TT	2240	2.5
15.5-38	12	TIP-10	14	397	1587	TT	1840	1.9
16.9-38	12	TIP-10	15	431	1687	TT	2240	1.7
18.4-38	12	TIP-10	16	469	1752	TT	2430	1.4

AVAILABLE SIZE



TIP-10



TIP-11

AVAILABLE SIZE

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	Cap Load (kgs)	IP BAR
11.2-28	8	TIP-11	10	284	1205	TT	1320	2.4
12.4-28	12	TIP-11	11	318	1272	TT	1650	2.5
13.6-28	8	TIP-11	12	345	1309	TT	1650	2
14.9-28	10	TIP-11	13	378	1365	TT	2020	2.1
16.9-28	12	TIP-11	15	432	1436	TT	2725	2.4
16.9-30	12	TIP-11	15	432	1483	TT	2300	1.7
18.4-30	12	TIP-11	16	469	1548	TT	2180	1.4
18.4-30	12	TIP-11	16	469	1548	TT	3250	2.3
23.1-26	16	TIP-11	20	587	1560	TL	4375	2.3

AVAILABLE SIZE

Size	Ply Rating	Pattern	Rim Width Inch	CSS (MM)	OD (MM)	TPYE	Cap Load (kgs)	IP BAR
23.1-26	16	TIP-12	20	587	1560	TL	4375	2.3



TIP-12

*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



AGRICULTURE IMPLEMENT TIRES

Size	Ply Rating	Pattern	Rim Width Inch	CSW (MM)	OD (MM)	Cap Load (kgs)	IP BAR
9.5L-14	8	TIP-13	7	240	735	1090	3
9.5L-15	8	TIP-13	7	240	770	1120	3
11L-14	8	TIP-13	8	265	750	1120	2.5
11L-15*	8	TIP-13	8	270	770	1150	2.5
11L-15	8	TIP-13	8	255	10	1150	2.5
11L-16	10	TIP-13	8	270	10.6	1310	3
12.5L-15	10	TIP-13	10	310	12.2	1550	3
12.5L-16	10	TIP-13	10	310	12.2	1600	3
16.5L-16.1	10	TIP-13	14	425	16.7	2360	2.5
400/60-15.5	14	TIP-13	13	400	875	2800	3.5

AVAILABLE SIZES



TIP-13

AVAILABLE SIZES

Size	Ply Rating	Pattern	Rim Width Inch	CSW (MM)	OD (MM)	Cap Load (kgs)	IP BAR
10.0/80-12	10	TIP-14	9	265	710	1285	3.9
10.0/75-15.3	12	TIP-14	9	272	762	1700	6
10.0/75-15.3	12	TIP-14	9	272	762	1900	7

Size	Ply Rating	Pattern	Rim Width Inch	CSW (MM)	OD (MM)	Cap Load (kgs)	IP BAR
11.5/80-15.3	14	TIP-15	9	295	846	2430	6.25

AVAILABLE SIZES



TIP-15



TIP-14

*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



SKIDSTEER / FORKLIFT / MPT TYRES

Size	Ply Rating	Pattern	Rim Width Inch	CSW (MM)	OD (MM)	Cap Load (kgs)	IP BAR
10.5/80-18	10	TIP-16	9	274	907	1550	5
12.5/80-18	12	TIP-16	9	306	989	2650	4.7



TIP-17



TIP-16

Size	Ply Rating	Pattern	Rim Width Inch	CSW (MM)	OD (MM)	Cap Load (kgs)	IP BAR
10-16.5	12	TIP-17	8.25	270	776	2375	6.2
12-16.5	12	TIP-17	9.75	312	825	2865	5.5

Size	Ply Rating	Pattern	Rim Width Inch	CSW (MM)	OD (MM)	Cap Load (kgs)	IP BAR
10-16.5		TIP-18	8.25	264 10.4	773 30.4	2130 4675	5.2 75
12-16.5		TIP-18	9.75	307 12.1	831 32.7	2900 6393t	5.5 80
19.5L-24		TIP-18					



TIP-18

*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



LIGHT COMMERCIAL BUS & PASSENGER CARS TYRES

AVAILABLE SIZES

Size	Ply Rating	Pattern	Rim Width Inch	Inflated Dim. (+/-) 2%		Cap Load (kgs)	IP BAR
				CSW (MM)	OD (MM)		
				600-16	10		
650-14	12	TIP-37 TIP-36	4.50J	595	148	825	4.15
F-78-15	8	TIP-37 TIP-37	5.55	685	188	825	4.15
700-15	12	TIP-35 TIP-33 TIP-37	5.50 F	772	190	1180	6.2
700-16	12	TIP-33	6	812	190	1215	6.2
750-15	12	TIP-33	6	805	210	1500	7.2
750-16	16	TIP-36 TIP-33 TIP-37	6	814	198	1600	7.6
825-16	16	TIP-33 TIP-34	6.5	844	206	1850	7.6



AVAILABLE SIZES

Size	Ply Rating	Pattern	Rim Width Inch	Inflated Dim. (+/-) 2%		Cap Load (kgs)	IP BAR
				CSW (MM)	OD (MM)		
				8.25-20	16		
9.00-20	16	TIP-37	7	1040	266	2570	7.95
		TIP-33					
		TIP-34					
9.00-20	18	TIP-37	7	1040	266	2650	7.95
		TIP-33					
		TIP-34					
10.00-20	16	TIP-37	7.5	1073	280	3000	7.95
		TIP-33					
		TIP-34					
10.00-20	18	TIP-37	7.5	1068	279	3080	7.95
		TIP-33					
		TIP-34					
11.00-20	18	TIP-37	8	1085	293	3250	7.95
		TIP-33					
		TIP-34					
12.00-20	18	TIP-37	8.5	1125	315	3750	7.95
		TIP-33					
		TIP-34					



*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



TRIMPHANT
IMPEX PRIVATE LIMITED

AVAILABLE SIZES

Size	Ply Rating	Pattern	Rim Width Inch	Inflated Dim.		Cap Load (kg)	IP BAR
				(+/-) 2%			
				CSW (MM)	OD (MM)		
3.50 - 8	4 PR	TIP-22	2.5	390	92	170	2.5
3.00 - 10	4 PR	TIP-22	2.1	421	81	150	2.5
3.00 - 12	6 PR	TIP-23	2.1	464	80	165	2.8
3.75-12	6 PR		1.85	526	80	165	2.8
3.00-14	6 PR	TIP-23	1.85	526	80	165	2.8
3.50 - 10	4 PR	TIP-29 TIP-22 ---	2.5	437	92	195	2.5
2.75 - 17	6 PR	TIP-19 TIP-20 TIP-28	1.85	588	75	175	2.8
2.75 - 18	4 PR	TIP-19 TIP-23 TIP-28 TIP-27	1.85	610	77	180	2.8
3.00 - 17	6 PR	TIP-26 TIP-27	1.85	602	80	190	2.8
3.00 - 18	6 PR	TIP-19 TIP-23 TIP-28 TIP-27	1.85	662	99	230	2.8
3.00 - 19	6 PR	TIP-19 TIP-27	1.85	652	82	215	2.8
3.50 - 19	6 PR	TIP-29	1.85	652	82	215	2.8
3.25 - 16	6 PR	TIP-19 TIP-26	2.15	588	89	218	2.8
3.25 - 19	6 PR	TIP-19 TIP-26	2.15	664	91	250	2.8
2.50 - 18	4 PR	TIP-27	1.6	593	65	140	2.25
100/90-17	4 PR	--- TIP-29	2.5	612	101	218	2.25
90/100 - 10	4 PR	TIP-28	2.15	438	92	206	2.5
90/90 - 12	6 PR	TIP-28	2.15	467	92	212	2.5
100/90 - 18	6 PR	---	2.5	641	102	224	2.25
120/80 - 17	6 PR	TIP-28	2.75	626	121	257	2.3

2 WHEELER TYRES



*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



TRIPHANT
INDIA PRIVATE LIMITED



3 WHEELER TYRES



AVAILABLE SIZES

Size	Ply Rating	Pattern	Rim Width Inch	Inflated Dim.		Cap Load (kgs)	IP BAR
				CSW (MM)	OD (MM)		
4.00-8	8	TIP-30 TIP-31 TIP-32	3	415	110	400	4.25
4.00-10	6	TIP-32	3	466	110	437	4.25
4.00-12	6	TIP-32A	3	530	112	250	3.4
4.50-10	8	TIP-30	3.5	490	125	515	5
4.50-12	8	TIP-32	3.5	529	122	257	2.1
5.00-10	8	TIP-32 TIP-30	3.5	516	134	580	5
5.00-12	8	---	3.5	516	134	590	5
5.20-14	6	TIP-30	3.5	612	132	375	2.1
5.50-13	6	TIP-30	4	600	145	387	2.1
5.60-13	6	TIP-30	4	600	145	387	2.1
5.65-12	6	TIP-32	4	522	131	272	2.1
5.90-15	6	TIP-32	4	668	150	462	2.1
155/80 D-12	8	TIP-30 TIP-32	4.5	546	151	412	4.5
165/80 D-13	8	TIP-30	4.5	597	165	670	4.5
165/80 D-14	8	TIP-30	4.5	620	165	575	2.4



*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



SOLID TIP 405

Tyre Size	RIM	Tread	Tire Dimension in mm			Load Capacity Fork Lift-upto 25 kmph	
			Outer Dia.	Sidewall Width	Tread Width	Load Wheel	Steer Wheel
15x4 1/2-8 (125/75-8)	3.00 3.25	LUG	368	105	90	1,040	800
5.00-8	3.00	LUG	450	120	110	1,415	1,090
16x6-8 (150 / 75-8)	4.33	LUG	406	140	125	1,270	975
18x7-8 (180 / 70-8)	4.33	LUG , RIB	450	157	142	2,145	1,650
6.00-9	4.00	LUG	520	138	120	1,885	1,450
21 / 8-9 (200 / 75-9)	6.00	LUG	517	188	157	2,755	2,120
6.50-10	5.00 , 5.50	LUG	566	160	140	2,340	1,800
7.50-10	5.00 , 5.50	LUG	630	170	150	3,070	2,360
23x9-10, (225 / 75-10)	6.50	LUG	580	194	178	3,160	2,430
7.00-12	5.00	LUG	646	172	150	2,920	2,240
23x10-12	8.00	LUG	580	232	200	3,770	2,900
27x10-12 (250 / 75-12)	8.00	LUG	672	240	200	3,900	3,000
7.00-15	5.50	LUG	705	180	158	3,545	2,725
7.50-15	5.50 , 6.00 , 6.50	LUG	736	193	168	3,900	3,000
8.15-15 (28x9-15) (225 / 75-15)	7.00	LUG	678	221	190	3,445	2,650
8.25-15	6.50	LUG	808	192	173	4,750	3,650
2.50-15 (250 / 70-15)	7.00 , 7.50	LUG	706	220	190	4,745	3,650
3.00-15 (315 / 70-15)	8.00	LUG	806	242	223	5,850	4,500
7.50-16	5.50,6.00,6.50	LUG	736	193	168	3,900	3,000
8.25-16	5.50,6.00	LUG	808	192	173	4,750	3,650
7.50-20	6.00	LUG	870	200	175	3,900	3,250
8.25-20	6.50	LUG	915	200	180	4,380	3,650
9.00-20	6.50,7.00	LUG	972	226	191	5,400	4,500
10.00-20	7.00,7.50, 8.00,8.50	LUG	1004	250	203	6,000	5,000
11.00-20	7.50,8.00,8.50	SM	1050	265	235	6,000	5,000
12.00-20	8.00,8.50	LUG	1080	255	232	7,560	6,300
12.00-20	8.00,8.50	SM	1140	295	250	7,560	6,300
12.00-24	8.50 , 10.00	LUG	1165	265	230	8,040	6,700
14.00-24	10.00	LUG	1275	308	270	11,100	9,250
14.00-25	10.00	LUG	1275	308	270	11,100	9,250

AVAILABLE SIZES

*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



TRIMPHANT
IMPEX PRIVATE LIMITED



PNEUMATIC TIP 406

Size	RIM (inch)	Alternate RIM (inch)	Inflated Dim. (mm) +/-2%		NSD		Ply Rating	Inflation Pressure		Load Capacity (kg) Fork Lift-up-to 25 kmph		
			OD	CROSS SW	mm	(32nd of inch)		Bar	psi	Load Wheel	Steer Wheel	Side Loaders
5.00-8	3.00	-	470	145	13.00	16.5 / 32	10	10.00	142	1415	1090	1645
16X6-8	4.33	-	420	158	12.50	15.5 / 32	18	10.50	150	1540	1185	1790
18X7-8	4.33	-	462	170	17.00	21.5 / 32	16	10.00	142	2145	1650	2490
21X8-9	6.00	7.00	535	210	18.00	22.5 / 32	16	10.00	142	2755	2120	3200
6.00-9	4.00	-	540	165	15.50	19.5 / 32	12	10.00	142	1885	1450	2190
6.50-10	5.00	5.50	598	190	15.50	19.5 / 32	12	9.00	128	2145	1650	2490
7.00-12	5.00	1	680	196	15.50	19.5 / 32	14	9.00	128	2755	2120	3200
23X9-10	7.00	-	590	235	18.50	23.5 / 32	20	10.00	142	3445	2650	4000
27X10-12	8.00	-	692	252	21.50	27.0 / 32	16	8.00	114	3900	3000	4530
23X10-12	8.00	-	605	260	15.50	19.5 / 32	18	9.00	128	3385	2605	3935
7.00-15	5.50	-	750	200	18.00	22.5 / 32	14	9.25	132	3280	2525	3810
7.50-15	6.00	5.50, 6.50	780	218	18.00	22.5 / 32	16	10.00	142	3810	2930	4425
8.15-15	7.00	-	725	219	18.00	22.5 / 32	14	10.00	142	3900	3000	4530
250-15	7.00	7.50	747	250	18.00	22.5 / 32	16	8.25	117	4355	3350	5060
300-15	8.00	-	840	300	22.00	27.5 / 32	18	7.50	107	5845	4495	6785
8.25-15	6.50	6.00 / 7.00	840	235	21.00	26.5 / 32	16	9.25	132	4615	3550	5345

AVAILABLE SIZES



*Specification may vary after final production.
*Pr & Pattern may different as real.
*Customize size welcome.



FLOTATION TYRES



BUTYL TUBES AVAILABLE BUTYL TUBES FOR

- 2 WHEELER TYRES
- 3 WHEELER TYRES
- LIGHT COMMERCIAL VEHICLE TYRES
- PASSENGER CARS TYRES
- TRUCK BUS TYRES
- AGRICULTURE TRACTOR TYRES
- OFF THE ROAD TYRES
- SKID STEER TYRES
- FORKLIFTS TYRES

AVAILABLE SIZES

Type Size	Pattern	Ply Rating	Rim Width Inch	CSW (MM)	OD (MM)	Free Rolling	Drive Rolling	IP BAR
						Load (kgs)	Load (kgs)	
400/60-22.5	TR-555	16	11.75	400	1070	4000	2800	3.5
550/45-22.5	TR-555	16	16	550	1070	4375	3075	2.8
550/50-22.5	TR-555	12	16	550	1230	4500	3150	2.1
600/50-22.5	TR-555	16	20	600	1170	5150	3650	2.6



*Specification may vary after final production.
 *Pr & Pattern may different as real.
 *Customize size welcome.



TRIMPHANT

TRIMPHANT
IMPEX PRIVATE LIMITED

Excellent Quality You Can Rely Upon



*Specification may vary after final production.
*Pr & Pattern may differ as real.
*Customize size welcome.



TRIMPHANT

TRIMPHANT
IMPEX PRIVATE LIMITED

Excellent Quality You Can Rely Upon



*Specification may vary after final production.
*Pr & Pattern may differ as per actual.
*Customize size welcome.



TRIMPHANT IMPEX PRIVATE LIMITED

Add.: 117P-1, 402, Shivpuri, Chhapera Puliya, Kanpur, Uttar Pradesh, India

E-mail.: exports@trimphant.com | Web.: www.trimphanttyres.com

Ph.: +91 730 390 8299

