



# PLUG VALVE



1/2" to 12" WCB/CF8/CF8M CF8/CF8M Temperature Up to 200°C 150#/300#/600#/800# Screwed/Flange





½" to 2" CF8/CF8M/ CF3M 3000 PSI Temperature Up to 100°C

#### 32 Medium Pressure Needle Valve



1/4" to 2" CF8/CF8M 350 Kg/cm<sup>2</sup> Temperature Up to 200°C



High Pressure Needle Valve		alve
	Model	4M-HNV- HP
	Size	1/4" to 2"
	MOC	Forged Steel / SS 304/316
	Pressure	700 Kg/cm <sup>2</sup>
	Temperature	Up to 360°C
	Ends	Screwed

#### 33 Globe Type Control Valve



4M-GMS/GMF 1/2" to 2" CF8 /CF8M /CF3M Pressure Up to 16 Bar Temperature Up to 3.5 to 7 Bar Ends Flanged

# 38 Globe Type Control Valve



4M-GMS /GMF ½" to 4" CF8 /CF8M /CF3M Up to 16 Bar Temperature Up to 3.5 to 7 Bar Screwed

### 34 Pharma Diaphragm Valve



4M-PDV 1/2" to 3" CF8M Up to 8Kg/cm<sup>2</sup> Temperature Up to 80°C

## 39 Knife Gate Valve



4M- NGM 2" to 24" MOC C.I/ WCB/CF8/CF8M C.I/WCB/CF8/CF8M PTFE/METAL Insp & Test Std MSS SP-81 (150#)(300#)(600#) Ends ASME B 16.5 RF(Lug Type)

## 35 Piston Valve



4M-UKL-FD 2.1/2" TO 8" C.I/ WCB CF8/CF8M Temperature Up to 400°C (150#)(300#) FLANGED to ASME B 16.5 RF

# 40 Disc Check Valve Non Slame Check Valve



4M-DNRV / DCV ½" to 12" MOC CF8 /CF8M /CF3M Metal to Metal/ Soft Seat Up to 42 Bar Temperature 300°C Metal to Metal 180°C Soft Seat Wafer /Screwed



- Process & Chemical
- Refineries & Petrochemicals
- Drugs & Pharmaceuticals
- Thermal Power Stations
- Dyes & Intermediates
- Breweries & Distilleries
- Steel Plants
- Solvent Extraction Plants
- Cooling Water
- Ship Yards & Marine Management
- LPG Bottling Plants

- Fertilizers
- Textiles
- Sugar



- Paints & Varnishes
- Soaps & Detergents
- Slurry & Ash Handling
- Food & Oil Industry
- Effluent & Water Treatment
- Water Works
- Pulp & Paper
- Onshore & Offshore Platforms















API CERTIFIED

#### **4MATIC VALVE AUTOMATION AFRICA LTD.**

Call: +254 753602070

4Matic

Email: 4matic.faizan@gmail.com/info@4maticvalves.com

■ Web: www.4maticvalves.com

www.4maticvalves.com

• KENYA • USA • INDIA • SINGAPORE











4Matic

Your Solution Partner in Industrial Manual Valves
















#### 3 Pcs Design Ball Valve (Metal seated) Handle & Gear Operated




#### Lever / Gear Operated 3 piece design 2 way ball valve Flanged



Model 4M-BAW/ IPH/3OKH/YEF Size ½" to 12" MOC WCB /CF8 /CF8M Ball Valve 3 Piece Design 150# & 300# Pressure 10 kg/cm<sup>2</sup> Temperature Up to 180°C Ends Flanged

#### 3 Pcs Design Ball Valve (Metal seated) Handle & Gear Operated




#### ever / Gear Operated 3 piece design 2 way ball valve Screwed



Model 4M-BAW/IPH/3OKH/YEF Size ½" to 4" MOC WCB /CF8 /CF8M Ball Valve 3 Piece Design Class 150# Pressure 10 kg/cm<sup>2</sup> Temperature Up to 180°C Ends Screwed

#### High Pressure Ball Valve -3000 WOG Pcs Design "VGO" Ball Valve Handle Operated



# andle & Gear Operated



Model 4MBMS-HD-SD/BMS-HD-FD ½" to 12" MOC WCB / CF8 / CF8M Ball Valve 2 Piece Design 150# & 300# Pressure 10 kg/cm<sup>2</sup> Temperature Up to 180°C Ends Screwed / Flanged

# Handle Operated



4M-KAD-HD ½" to 4" WCB / CF8 / CF8 M Pressure 10 Kg/cm<sup>2</sup> Temperature Up to 220°C Ends Wafer Type



4M-WTB-HD ½" to 4" WCB / CF8 /CF8M Pressure 10 Kg/cm<sup>2</sup> Temperature Up to 180°C Ends Flanged

# Handle Operated 3 Way AWA Series



Model 4M-AWA Size ½" to 2" MOC Cast Steel/CF8 /CF8M Pressure Up to 500 Kg Temperature Up to 80°C (High Temp. Available) Screwed

# andle Operated 2 Way AWA Series



4M-AWA Model ½"to 2" Cast Steel / CF8/CF8M Pressure Upto 500 Kg/cm<sup>2</sup> Temperature Up to 150°C Ends Screwed

#### 3 Way "C" Way Design Ball Valve Handle & Gear Operated



4M-CWP-HD-SD/ CWP-HD-FD 1" to 4" WCB/CF8/CF8M Ball Valve "C" Type Design Class 150# Pressure 10 kg/cm<sup>2</sup> Temperature Up to 180°C Screwed/ Flanged

3 & 4 Way Ball Valve

Handle & Gear Operated 4M-SUZ-HD-FD Model Size 1/2" to 12" MOC WCB/CF8/CF8M 150# & 300# 10 kg/cm<sup>2</sup> Temperature Up to 180°C Flanged/ Triclover End/Socket Weld

Size

MOC

Class

Flush Bottom Ball Valve Reduce Bore

MOC

#### 12 SINGLE PIECE BALL VALVE -1000 WOG



4M-SPBV 8mm to 100mm CF8/ CF8M CF8/CF8M Stem CF8/CF8M Seat & Seal PTFE Ends Screwed to (BSPF)(NPTF)

#### 3 & 4 Way Ball Valve Handle & Gear Operated



4M-SUZ-HD-SD 1/2" to 4" WCB/CF8/CF8M 150# & 300# Pressure 10 kg/cm<sup>2</sup> Temperature Up to 180°C Screwed / Triclover End/Socket Weld

#### FEP / PFA Lined Ball Valve 13 Handle Operated



4M-FELB Model 1" to 4" Size C.I./ WCB /CF8 /CF8M MOC As Per Customer Pressure Requiremnet Temperature FEP 180°C/PFA 230°C Ends Flanged

# **UPVC Ball Valve**



4M-BMW-UPVC-SD 1/2" to 4" Size MOC UPVC Pressure Up to 7 Kg/cm<sup>2</sup> Temperature Up to 80°C Ends Screwed

4M-FBB

Pressure Up to 10 Kg/cm<sup>2</sup>

Temperature Up to 180°C

Ends Flanged

WCB /CF8 /

CF8M/CF3M

6"X8"/8"X10"/10"X12"

#### ff Set Disc Wafer Type Butterfly Valve Handle & Gear Operated



15 Handle Operated

4M-BOD 2.½" to 48" WCB / CF8 /CF8M Pressure PN 10 / PN 16 Temperature NBR-10°C to 90°C EPDM-20°C to 120°C Viton 0°C to 220°C PTFE-50°C to 180°C Ends Wafer Type


4M-KAG-HD

1" to 4"

Pressure 10 Kg/cm<sup>2</sup>

Temperature Up to 180°C

Ends Wafer Type



#### landle & Gear Operated 4M-AFT-MS-G Size 8" to 80" MOC Steel Fabricated Seals Metal ti Metal Pressure PN 10/ PN 16 Temperature Up to 450°C

# **4Matic**

#### ff Set Disc Double Flange Butterfly Valve Handle & Gear Operated



4M-DOB 2.½" to 72" WCB / CF8 / CF8 M Pressure PN 10 / PN 16 Temperature NBR-10°C to 90°C EPDM-20°C to 120°C Viton 0°C to 220°C PTFE-250°C to 180°C

#### oherical Disc Valve Handle & Gear Operated



4M-SDV Size 1.½" to 48" MOC WCB / CF8 /CF8M Pressure ANSI 150 Class Temperature Up to 180°C Ends Wafer Type

# **Butterfly Valve Handle & Gear Operated**



4M-FEP-PFA Model 2" to 12" MOC WCB / CF8 / CF8 M/C.I. Pressure PN 10 Temperature FEP 180°C/ PFA 230°C Ends Wafer Type

#### Lug Type Butterfly Valve Centric Disc Design Handle & Gear Operated



Model 4M-FLB Size 1.1/2" to 72" MOC CI/DI/WCB/CF8/CF8M Disc Nitrile/NBR/EPDM/Vitor Pressure PN 6/10/20 & 25 Temperature -20°C to 70°C Ends Lug Type

#### **UPVC Butterfly Valve** 23



4M-ECO-UPVC 2" to 8" UPVC MOC Pressure Up to 7 Kg/cm<sup>2</sup> Temperature Up to 80°C Ends Wafer Type

#### iple Offset Butterfly Valve andle & Gear Operated



4M-TOB Model 2" to 48" WCB / CF8 /CF8M MOC Metal to Metal Pressure Up to 10 Kg/cm<sup>2</sup> Temperature Up to 40 to 600°C Ends Wafer / Lug Type

# Butterfly Valve Handle & Gear Operated



Model 4M-ITC 2" to 12" MOC WCB / CF8 / CF8 M/C.I. Pressure PN 10 Temperature 160°C Ends Wafer Type

# 29 Handle Operated



Model 4M-BFV-ALL Size 1.1/2" to 12" MOC Alluminium Press, Die Cast Disc CF8M Pressure 8 Kg/cm<sup>2</sup> Temperature Up to 120°C Ends Wafer / Lug Type

#### afer Type Double Flange Butterfly Valve andle & Gear Operated



4M-DFW-ECO 3" to 72" MOC S.G. Iron/C.I./CF8/CF8M Seals Nitrile /EPDM /Viton Pressure PN 10 Temperature -25°C to 80°C Ends Double Flange

# andle & Gear Operated



4M-DP-HD 1.1/2" to 20"(Upto 8"Handle) MOC S.G. Iron/C.I./CF8/CF8M Metal to Metal Pressure PN 10 Temperature -25°C to 400°C (Depending on MOC) Water Type

















lush Bottom Ball Valve

Model

MOC

Size





Ends Double Flanged









